

## Spezifikation / Specification

<b>Schaum / Foam :</b>	<b>Cellpur R 5025</b>																																																																							
<b>Farbe / Colour :</b>	mint / mint																																																																							
<b>Artikel Nr. / Article no. :</b>	750104																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th> <th style="width: 10%;"></th> <th style="width: 10%;"></th> <th style="width: 10%;">Minimum</th> <th style="width: 10%;">Maximum</th> <th style="width: 10%;"></th> </tr> </thead> <tbody> <tr> <td>Materialdichte netto / Net Density</td> <td></td> <td>EN ISO 845</td> <td>45,0</td> <td>50,0</td> <td>[ kg / m<sup>3</sup> ]</td> </tr> <tr> <td>Stauchhärte / Compression Load Deflection (CLD)</td> <td>40% press</td> <td>EN ISO 3386-1</td> <td>2,5</td> <td>3,0</td> <td>[ kPa ]</td> </tr> <tr> <td>Elastizität / Elasticity</td> <td></td> <td>DIN 53 573</td> <td>70</td> <td>...</td> <td>[ % ]</td> </tr> <tr> <td>Zugfestigkeit / Tensile Strength</td> <td></td> <td>EN ISO 1798</td> <td>80</td> <td>...</td> <td>[ kPa ]</td> </tr> <tr> <td>Dehnung / Elongation At Break</td> <td></td> <td>EN ISO 1798</td> <td>100</td> <td>...</td> <td>[ % ]</td> </tr> <tr> <td>Luftdurchlässigkeit / Air Permeability</td> <td></td> <td>ASTM D 1564</td> <td>0</td> <td>...</td> <td>[ L / min ]</td> </tr> <tr> <td>Wet Compression Set</td> <td>(50 °C, 95 % rel, 70 % press, 22 h)</td> <td>Renault 1637</td> <td>...</td> <td>15</td> <td>[ % ]</td> </tr> <tr> <td>Compression Set</td> <td>(70 °C, 50 % rel, 50 % press, 22 h)</td> <td>EN ISO 1856-A</td> <td>...</td> <td>...</td> <td>[ % ]</td> </tr> <tr> <td>DVR / Compression Set B</td> <td>(23 °C, 50 % rel, 50 % press, 72 h)</td> <td>EN ISO 1856-B</td> <td>...</td> <td>...</td> <td>[ % ]</td> </tr> <tr> <td>Eindrückhärte / Indentation Load Deflection (ILD)</td> <td>40% press</td> <td>EN ISO 2439-C</td> <td>...</td> <td>...</td> <td>[ N ]</td> </tr> </tbody> </table>									Minimum	Maximum		Materialdichte netto / Net Density		EN ISO 845	45,0	50,0	[ kg / m <sup>3</sup> ]	Stauchhärte / Compression Load Deflection (CLD)	40% press	EN ISO 3386-1	2,5	3,0	[ kPa ]	Elastizität / Elasticity		DIN 53 573	70	...	[ % ]	Zugfestigkeit / Tensile Strength		EN ISO 1798	80	...	[ kPa ]	Dehnung / Elongation At Break		EN ISO 1798	100	...	[ % ]	Luftdurchlässigkeit / Air Permeability		ASTM D 1564	0	...	[ L / min ]	Wet Compression Set	(50 °C, 95 % rel, 70 % press, 22 h)	Renault 1637	...	15	[ % ]	Compression Set	(70 °C, 50 % rel, 50 % press, 22 h)	EN ISO 1856-A	...	...	[ % ]	DVR / Compression Set B	(23 °C, 50 % rel, 50 % press, 72 h)	EN ISO 1856-B	...	...	[ % ]	Eindrückhärte / Indentation Load Deflection (ILD)	40% press	EN ISO 2439-C	...	...	[ N ]	
			Minimum	Maximum																																																																				
Materialdichte netto / Net Density		EN ISO 845	45,0	50,0	[ kg / m <sup>3</sup> ]																																																																			
Stauchhärte / Compression Load Deflection (CLD)	40% press	EN ISO 3386-1	2,5	3,0	[ kPa ]																																																																			
Elastizität / Elasticity		DIN 53 573	70	...	[ % ]																																																																			
Zugfestigkeit / Tensile Strength		EN ISO 1798	80	...	[ kPa ]																																																																			
Dehnung / Elongation At Break		EN ISO 1798	100	...	[ % ]																																																																			
Luftdurchlässigkeit / Air Permeability		ASTM D 1564	0	...	[ L / min ]																																																																			
Wet Compression Set	(50 °C, 95 % rel, 70 % press, 22 h)	Renault 1637	...	15	[ % ]																																																																			
Compression Set	(70 °C, 50 % rel, 50 % press, 22 h)	EN ISO 1856-A	...	...	[ % ]																																																																			
DVR / Compression Set B	(23 °C, 50 % rel, 50 % press, 72 h)	EN ISO 1856-B	...	...	[ % ]																																																																			
Eindrückhärte / Indentation Load Deflection (ILD)	40% press	EN ISO 2439-C	...	...	[ N ]																																																																			
<b>Brandverhalten / Fire Resistance</b>																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td rowspan="10" style="width: 20%; vertical-align: top;">                     EUFAC Test (Cigarette)                 </td> <td style="width: 20%;"></td> <td style="width: 10%;">EN 1021-1</td> <td style="width: 10%;">OK</td> <td style="width: 10%;">...</td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td>EN 1021-2</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>UNI 9175</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>California 117 (2000)</td> <td>OK</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>MVSS 302</td> <td>OK</td> <td>SE</td> <td></td> </tr> <tr> <td></td> <td>EN ISO 13501-1</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td rowspan="5" style="vertical-align: top;">                     Vertical Test 12 sec.                 </td> <td style="vertical-align: top;">                     FAR 25.853 + smoke + toxicity                 </td> <td></td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>DIN 5510-2</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>DIN 4102-1</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>BS 5852 Crib 5</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>ÖNORM A 3800</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>ÖNORM S 1457</td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td></td> <td>CH 5.2.</td> <td>...</td> <td>...</td> <td></td> </tr> </tbody> </table>						EUFAC Test (Cigarette)		EN 1021-1	OK	...			EN 1021-2	...	...			UNI 9175	...	...			California 117 (2000)	OK	...			MVSS 302	OK	SE			EN ISO 13501-1	...	...		Vertical Test 12 sec.	FAR 25.853 + smoke + toxicity		...	...			DIN 5510-2	...	...			DIN 4102-1	...	...			BS 5852 Crib 5	...	...			ÖNORM A 3800	...	...			ÖNORM S 1457	...	...			CH 5.2.	...	...	
EUFAC Test (Cigarette)		EN 1021-1	OK	...																																																																				
		EN 1021-2	...	...																																																																				
		UNI 9175	...	...																																																																				
		California 117 (2000)	OK	...																																																																				
		MVSS 302	OK	SE																																																																				
		EN ISO 13501-1	...	...																																																																				
	Vertical Test 12 sec.	FAR 25.853 + smoke + toxicity		...	...																																																																			
			DIN 5510-2	...	...																																																																			
			DIN 4102-1	...	...																																																																			
			BS 5852 Crib 5	...	...																																																																			
		ÖNORM A 3800	...	...																																																																				
	ÖNORM S 1457	...	...																																																																					
	CH 5.2.	...	...																																																																					
<b>sonstige / other</b>																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="width: 50%;">ÖKO-TEX Standard 100</td> <td style="width: 10%;"></td> <td style="width: 10%;">OK</td> <td style="width: 10%;">product class 1</td> <td style="width: 10%;"></td> </tr> <tr> <td>CertiPur Standard</td> <td></td> <td>OK</td> <td>...</td> <td></td> </tr> <tr> <td>IKEA IOS-MAT-0010</td> <td></td> <td>...</td> <td>...</td> <td></td> </tr> <tr> <td>EN / IEC 61340-5-1</td> <td>electrostatic 100 V , 20 sec</td> <td>...</td> <td>...</td> <td>Ohm [ Ω ]</td> </tr> </tbody> </table>						ÖKO-TEX Standard 100		OK	product class 1		CertiPur Standard		OK	...		IKEA IOS-MAT-0010		...	...		EN / IEC 61340-5-1	electrostatic 100 V , 20 sec	...	...	Ohm [ Ω ]																																															
ÖKO-TEX Standard 100		OK	product class 1																																																																					
CertiPur Standard		OK	...																																																																					
IKEA IOS-MAT-0010		...	...																																																																					
EN / IEC 61340-5-1	electrostatic 100 V , 20 sec	...	...	Ohm [ Ω ]																																																																				
<b>erstellt / created</b>	<b>letzte Änderung / last change</b>		<b>Freigabe / free</b>																																																																					
04.07.2012	23.04.2013		23.04.2013																																																																					
QM	QM		QM																																																																					